


BUS DI CAMPO FIELDBUS



COS'È UN BUS DI CAMPO

Fieldbus

IEC 61158


ControlNet




EtherCAT 

HART 


BUS DI CAMPO - TOPOLOGIA




Ring



Branch



Star




Daisy Chain

BUS DI CAMPO – RS 232



BUS DI CAMPO – OGGI




COS'È UN BUS DI CAMPO

Fieldbus

IEC 61158


ControlNet




EtherCAT 

HART 


COS'È UN BUS DI CAMPO



COS'È UN BUS DI CAMPO




COS'È UN BUS DI CAMPO



PROFIBUS-DP

Profibus: Process Field Bus

DP: Decentralized Peripherals




SIMATIC S7-1200

Laptop

HMI


Modem

VFD




RS-485







PROFIBUS-DP




PROFIBUS-DP




PROFIBUS-DP




PROFIBUS-DP



PROFIBUS-DP



PROFIBUS-DP



PROFIBUS Vs PROFINET




Bus di Campo Seriale




Protocollo Ethernet Industriale


PROFI[®]
BUS




1989



PROFI[®]
NET




2000s




SIEMENS

**PROFI
BUS**




**PROFI
NET**



PROFI[®]
BUS





PROFI[®]
NET








PROcess **Field** **BUS**







PROFI BUS




**PROFI
BUS**




PLC S7-400




PLC S7-300



ET 200S





DP/PA Coupler







Serial Communication: RS-485

Masters




PLC: Programmable Logic Controller
PAC: Programmable Automation Controller
DCS: Distributed Control System


Slaves



PROFI BUS



- ET200
 - Add new device
 - Devices & networks
 - PLC_1 [CPU 319-3 PN/DP]
 - Ungrouped devices
 - Unassigned devices
 - Common data
 - Documentation settings
 - Languages & resources
 - Online access
 - Card Reader/USB memory



Slave_1 [IM 151-1 Standard]

General IO tags System constants Texts

General

- PROFIBUS address
- Module parameters
- Option handling
- SYNC/FREEZE
- Diagnostics addresses

PROFIBUS address _____

Interface networked with

Subnet: PROFIBUS_1

Add new subnet


Parameters

Address: 1

Highest address: 126

Transmission speed: 1.5 Mbps



PROFI BUS



PROFI BUS



9600 bps – 1000 m



12 Mps – 50 m









DP: Decentralized Periphery

PA: Process Automation




Physical Layer: Manchester-encoded Bus Powered (MBP)







PROFI
NET




PROFI NET



RJ-45 Ethernet Jack

PROFI
NET



PROFI NET




100 Mps – 100 m

Tempo di Risposta < 1ms

**PROFI
NET**



Standard Ethernet Switch







Communication Medium: Standard Ethernet

Controllers




PLC: Programmable Logic Controller
PAC: Programmable Automation Controller
DCS: Distributed Control System

Devices





PROFINET



Types of Addresses in Profinet Devices


- IP Address
- MAC Address
- Device Name

PROFINET




Device Name	HMI_1	PLC_1	Drive_1	IE-PB_1
IP Address	192.168.0.1	192.168.0.2	192.168.0.3	192.168.0.4
MAC Address	28-63-36-0E-F6-E8	00-1C-06-0B-F2-46	00-1F-F8-F4-70-89	00-00-24-1A-35-C8


PROFI
NET




Line




Star



Tree




Ring




Technical Comparison

	PROFIBUS	PROFINET
Speed	12 Mbit/s	100 Mbit/s
Telegram Size	244 bytes	1440 bytes
Address Space	126	Unlimited
Communication Technology	Master/Slave	Consumer/Provider

Master-Slave Interaction



Consumer-Provider Model





Discrete



Process




Hybrid



Motion Control

FUNZIONAMENTO DI PROFINET





7 Application Layer

6 Presentation Layer

5 Session Layer


4 Transport Layer

3 Network Layer

2 Data Link Layer

1 Physical Layer


**MODELLO
Iso/Osi**



—————▶ **Higher performance requirements**

TCP/IP

UDP/IP





Configuration
Parameterization




Time-critical
tasks



RT= Real Time



PROFINET RT EtherType: 0x8892



PROFINET Isochronous Real Time


OPTIONAL

Enhanced rules:

Bandwidth reservation
Scheduling
Synchronization


Cycle times down to 31.25 μ s
Expected delays (jitter): 1 μ s





 **PROFINET RT**





TSN: Time Sensitive Networking




4th PROFINET communication channel:
PROFINET over TSN




Real time
communication



Low latency
networks




Plug&Work Networks




Converged
data
transport for OT and IT



Robustness, even with
high network loads



Using standard chips



ETHERCAT

EtherCAT

Ethernet for Control Automation Technology

EtherCAT

Data Frame


Tempi di Risposta Rapidi

Requisiti Minimi per Dispositivi

Costi di Implementazione


OSI Model


7	Application
6	Presentation
5	Session
4	Transport
3	Network
2	Data Link
1	Physical




Ethernet


EtherCAT









Distributed Clock System



ETHERCAT – TOPOLOGIA DI RETE




Star




Tree





Line




Bus










Modicon










Modbus Organization







Modbus




Master




Slave





Slave






Slave





























Master



21 001101







Memory Registers

10 | 01 | 11 | 00

Inputs	Outputs
01	00
00	10
10	11
11	01


Control

Monitor


Configure


VFD

Altivar 68-R




Modbus Device






01100011




Protocol Data Unit (PDU)



Reference	Action	Description
0xxx	Read/Write	Coils Outputs
1xxx	Read	Discrete Inputs
3xxx	Read	Input Registers
4xxx	Read/Write	Holding Registers





Function Code	Action	Table name
01 (01 hex)	Read	Discrete output coils
05 (05 hex)	Write single	Discrete output coil
15 (0F hex)	Write multiple	Discrete output coils
02 (02 hex)	Read	Discrete output contacts
04 (04 hex)	Read	Analog input contacts
03 (03 hex)	Read	Analog output holding registers
06 (06 hex)	Write single	Analog output holding register
16 (10 hex)	Write multiple	Analog output holding registers


Slave Address

Function Code
255


1 Byte

Data


CRC
Error Check



Master



VFD Altivar 68-R Slave




Slave Address

Function Code
03

Data
0000



CRC
Error Check




Master




Function Code	
00 00 00 11	Read Holding Registers





MOXA



Hms



ProSoft

